

Description

Fastener Length: 7/8", roughly 165 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20427M514
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-264-4437
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



P/N MS20427M5-14 Specifications

Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.257 Inches Minimum And 0.298 Inches Maximum
Grip Length:	0.641 Inches Nominal
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy R-405 Overall Or Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec All Material Responses Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M5-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.