

Description

length: 1", diameter: 5/32", 100°, countersunk head - monel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS20427M516 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-118-2014 |
| National Motor Freight: | 139820, Nickel Bolts / Nails / Nuts / Rivets Etc |

NO IMAGE
AVAILABLE

P/N MS20427M5-16 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.155 Inches Minimum And 0.159 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.257 Inches Minimum And 0.298 Inches Maximum |
| Grip Length: | 0.766 Inches Nominal |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M5-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.