

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20427M5C6
Minimum Qty (MOQ):	95 EA
NSN:	5320-00-080-0569
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20427M5C6 Specifications

Fastener Length:	0.375 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.156 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.257 Inches Minimum And 0.298 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Nickel Alloy 400 Overall
Material Document And Classification:	Qq-n-281 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall Or Zinc Overall Or Chromate Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M5C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.