

**Description**

Fastener Length: 1-1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20427M618
Minimum Qty (MOQ):	25 EA
NSN:	5320-00-852-5323
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



\* See page 2 for technical characteristics

## P/N MS20427M6-18 Specifications

<b>Fastener Length:</b>	1.125 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.188 Inches Nominal
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.323 Inches Nominal
<b>Grip Length:</b>	0.844 Inches Nominal
<b>Shear Strength:</b>	49000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M6-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.