

**Description**

length: 3/8", diameter: 3/16", 100°, countersunk head - monel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20427M66                                  |
| Minimum Qty (MOQ):      | 1 Pound                                     |
| NSN:                    | 5320-00-118-2016                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

## P/N MS20427M6-6 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.365 Inches Minimum And 0.385 Inches Maximum                                  |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.186 Inches Minimum And 0.190 Inches Maximum                                  |
| <b>Shank Style:</b>         | Straight   |
| <b>Head Major Diameter:</b> | 0.323 Inches Minimum And 0.365 Inches Maximum                                  |
| <b>Grip Length:</b>         | 0.094 Inches Nominal   |
| <b>Shear Strength:</b>      | 49000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>   | 98.5 Degrees Minimum And 101.5 Degrees Maximum                                 |
| <b>Material:</b>            | Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall                         |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M6-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.