

Description

length: 9/16", diameter: 3/16", 100°, countersunk head - monel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS20427M69 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-239-7831 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N MS20427M6-9 Specifications

| | |
|-------------------------------------|--|
| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.186 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.323 Inches Minimum And 0.355 Inches Maximum |
| Grip Length: | 0.281 Inches Nominal |
| Shear Strength: | 49000 Single Pounds Per Square Inch |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 400 Overall Or Nickel Alloy R-405 Overall |
| Nondefinitive Spec/std Data: | 3 Type And E Grade |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20427M6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.