

# P/N MS20470A2-12

### **Description**

Fastener Length: 3/4", roughly 4,000 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS20470A212

Minimum Qty (MOQ): 1 Pound

NSN: 5320-01-048-3283

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470A2-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.027 Inches Minimum And 0.037 Inches Maximum
Shank Diameter:	0.061 Inches Minimum And 0.065 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.119 Inches Minimum And 0.131 Inches Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12">https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12">https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12">https://military-fasteners.com/rivets/solid+rivets/MS20470A2-12</a> and selecting the quantity you want then