

Description

length: 3/4", diameter: 3/32", universal head, 1100-f aluminum, roughly 1630 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470A312
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-660-1295
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20470A3-12 Specifications

Fastener Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Grip Length:	0.599 Nominal Mils And 0.619 Nominal Centimeters
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470A3-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.