

# P/N MS20470A4-10

013630, Alum Rivets

### **Description**

length: 5/8", diameter: 1/8", universal head, 1100-f aluminum

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

National Motor Freight:

SKU / Model:	MS20470A410
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-234-8569
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470A4-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.062 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470A4-10">https://military-fasteners.com/rivets/solid+rivets/MS20470A4-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.