

**Description**

length: 5/8", diameter: 3/16", universal head, aluminum, roughly 415 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20470A610         |
| Minimum Qty (MOQ):      | 1 Pound             |
| NSN:                    | 5320-01-030-9997    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N MS20470A6-10 Specifications

|  |  |
|--|--|
| <b>Fastener Length:</b>                      | 0.615 Inches Minimum And 0.635 Inches Maximum      |
| <b>Head Style:</b>                           | Universal  |
| <b>Head Height:</b>                          | 0.080 Inches Minimum And 0.090 Inches Maximum      |
| <b>Shank Diameter:</b>                       | 0.186 Inches Minimum And 0.191 Inches Maximum      |
| <b>Shank Style:</b>                          | Straight   |
| <b>Head Major Diameter:</b>                  | 0.356 Inches Minimum And 0.394 Inches Maximum      |
| <b>Heat Treatment:</b>                       | Annealed Overall                                   |
| <b>Material:</b>                             | Aluminum Alloy 1100 Overall                        |
| <b>Material Document And Classification:</b> | Qq-a-430 Fed Spec Single Material Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470A6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.