

P/N MS20470A6-10

Description

length: 5/8", diameter: 3/16", universal head, aluminum, roughly 415 pieces per pound, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470A610
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-030-9997
ECCN:	EAR99
National Motor Freight:	013630. Alum Rivets



^{*} See page 2 for technical characteristics

P/N MS20470A6-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Heat Treatment:	Annealed Overall
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20470A6-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.