

Description

length: 5/16", diameter: 3/16", universal head, 1100-f aluminum, roughly 650 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470A65 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-242-1581 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470A6-5 Specifications

| | |
|--|---|
| Fastener Length: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| End Item Identification: | Helicopter, Chinook, Ch-47; Aircraft, T-37; Aircraft, Hercules C-130; Aircraft, Stratolifter C-135; Aircraft, Mh-47e Special Operations |
| Grip Length: | 0.021 Inches Minimum And 0.041 Inches Maximum |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470A6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.