

Description

length: 5/16", diameter: 3/16", universal head, 1100-f aluminum, roughly 650 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470A65
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-242-1581
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20470A6-5 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
End Item Identification:	Helicopter, Chinook, Ch-47; Aircraft, T-37; Aircraft, Hercules C-130; Aircraft, Stratolifter C-135; Aircraft, Mh-47e Special Operations
Grip Length:	0.021 Inches Minimum And 0.041 Inches Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470A6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.