

# P/N MS20470A8-16

### **Description**

length: 1", diameter: 1/4", universal head - 1100-f aluminum

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20470A816
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-242-0350
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470A8-16 Specifications

Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.254 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Material:	Aluminum Alloy 1100 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470A8-16">https://military-fasteners.com/rivets/solid+rivets/MS20470A8-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.