

Description

length: 1", diameter: 1/4", universal head - 1100-f aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470A816 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-242-0350 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470A8-16 Specifications

| | |
|--|--|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.254 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Grip Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Material: | Aluminum Alloy 1100 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470A8-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.