

Description

Fastener Length: 1-3/4", universal head, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD1028
Minimum Qty (MOQ):	5
NSN:	5320-00-257-4108
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470AD10-28 Specifications

Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Universal
Head Height:	0.133 Inches Minimum And 0.143 Inches Maximum
Shank Diameter:	0.311 Inches Minimum And 0.316 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.594 Inches Minimum And 0.656 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD10-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.