

**Description**

Fastener length: 1/4", universal head, roughly 9250 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | MS20470AD24         |
| Minimum Qty (MOQ):      | 1 Pound             |
| NSN:                    | 5320-00-243-8356    |
| Schedule B:             | 7616.10.3000        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N MS20470AD2-4 Specifications

|   |  |
|---|--|
| <b>Fastener Length:</b>                               | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| <b>Head Style:</b>                                    | Universal  |
| <b>Head Height:</b>                                   | 0.027 Inches Minimum And 0.037 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.061 Inches Minimum And 0.065 Inches Maximum  |
| <b>Shank Style:</b>                                   | Straight W/radius Chamfered Tip  |
| <b>Head Major Diameter:</b>                           | 0.119 Inches Minimum And 0.131 Inches Maximum  |
| <b>Material:</b>                                      | Aluminum Alloy 2117 Overall  |
| <b>Surface Treatment:</b>                             | Anodize Overall Or Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD2-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.