

# P/N MS20470AD3-10

### **Description**

length: 5/8", diameter: 3/32", universal head, aluminum alloy, roughly 1890 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20470AD310
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6821
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470AD3-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.094 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Material:	Aluminum Alloy Overall
Surface Treatment:	Anodize Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470AD3-10">https://military-fasteners.com/rivets/solid+rivets/MS20470AD3-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.