

**Description**

Fastener Length: 1 1/2", roughly 890 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20470AD324
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-011-6557
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N MS20470AD3-24 Specifications

<b>Fastener Length:</b>	1.500 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.027 Inches Minimum And 0.037 Inches Maximum
<b>Shank Diameter:</b>	0.062 Inches Nominal
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.119 Inches Minimum And 0.131 Inches Maximum
<b>Grip Length:</b>	1.406 Inches Nominal
<b>Shear Strength:</b>	26000 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Mil-t-5674 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD3-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.