

P/N MS20470AD4-26

Description

Fastener Length: 1-5/8", roughly 425 pieces per pound

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS20470AD426

Minimum Qty (MOQ): 100

NSN: 5320-01-391-2201

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









^{*} See page 2 for technical characteristics

P/N MS20470AD4-26 Specifications

| Identification Code Color: | Yellow |
|--|--|
| Fastener Length: | 1.602 Inches Minimum And 1.622 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Nominal |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Heat Treatment: | T-4 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541, Cl 1a Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26 and selecting the quantity you want then