

## P/N MS20470AD4-26

## **Description**

Fastener Length: 1-5/8", roughly 425 pieces per pound

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS20470AD426

Minimum Qty (MOQ): 100

NSN: 5320-01-391-2201

Schedule B: 7616.10.3000

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470AD4-26 Specifications

Identification Code Color:	Yellow
Fastener Length:	1.602 Inches Minimum And 1.622 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541, Cl 1a Mil Spec Single Treatment Response Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26">https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26">https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26">https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-26</a> and selecting the quantity you want then