

# P/N MS20470AD4-4

Military-Fasteners.com

#### Description

Length: 1/4", diameter: 1/8", universal head, aluminum alloy, roughly 1850 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### Additional Information

SKU / Model:	MS20470AD44
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-6826
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



## P/N MS20470AD4-4 Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.052 Nominal Mils And 0.072 Nominal Centimeters
Shear Strength:	26000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall

### How to Order

Order this solid rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.