

Description

length: 9/32", diameter: 1/8", universal head, aluminum alloy, roughly 1920 pieces per pound, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD445
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-005-6279
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470AD4-4.5 Specifications

Fastener Length:	0.271 Inches Minimum And 0.291 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Minimum Tensile Strength:	38000 Pounds Per Square Inch
Minimum Yield Strength:	18000 Pounds Per Square Inch
Shear Strength:	26000 Single Pounds Per Square Inch
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-4.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.