

Description

Fastener Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD44D5
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-497-5119
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20470AD4-4D-5 Specifications

Fastener Length:	0.396 Inches Minimum And 0.416 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.125 Inches Nominal
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	F/a-18 Hornet; Cbr Ecp-904
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Comp 2117 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type 2, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas-20470 Professional/industrial Association Standard

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-4D-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.