

Description

Fastener Length: 5/16", roughly 1650 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD45A
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-583-0746
Schedule B:	7616.10.3000
ECCN:	EAR99



P/N MS20470AD4-5A Specifications

Fastener Length:	0.303 Inches Minimum And 0.323 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Part Name Assigned By Controlling Agency:	Rivet Sold Universal Head Alluminum Alloy
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430, 2117-t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class I Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-5A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.