

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | MS20470AD49A |
| Minimum Qty (MOQ): | 250 EA |
| NSN: | 5320-01-494-2259 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N MS20470AD4-9A Specifications

| | |
|---|--|
| Fastener Length: | 0.553 Inches Minimum And 0.573 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.108 Inches Nominal |
| Shank Style: | Straight W/chamfered Tip |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Material: | Aluminum Alloy 2117 Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625, Type 2, Class 1 Mil Spec Single Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-9A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.