

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD49D
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-367-4744
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20470AD4-9D Specifications

Fastener Length:	0.5620 Inches Minimum And 0.5720 Inches Maximum
Head Style:	Universal
Head Height:	0.0540 Inches Minimum And 0.0640 Inches Maximum
Shank Diameter:	0.1250 Inches Nominal
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.2380 Inches Minimum And 0.2620 Inches Maximum
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-s-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-9D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.