

**Description**

Fastener Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470AD49D
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-367-4744
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470AD4-9D Specifications

<b>Fastener Length:</b>	0.5620 Inches Minimum And 0.5720 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.0540 Inches Minimum And 0.0640 Inches Maximum
<b>Shank Diameter:</b>	0.1250 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.2380 Inches Minimum And 0.2620 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-8625,ty 2,cl 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD4-9D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.