

**Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS20470AD512D                               |
| Minimum Qty (MOQ):      | 200 EA                                      |
| NSN:                    | 5320-01-485-5840                            |
| Schedule B:             | 7616.10.3000                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470AD5-12D Specifications

|  |   |
|--|---|
| <b>Fastener Length:</b>                | 0.750 Inches Nominal                          |
| <b>Head Style:</b>                     | Brazier                                       |
| <b>Head Height:</b>                    | 0.040 Inches Nominal                          |
| <b>Shank Diameter:</b>                 | 0.178 Inches Minimum And 0.196 Inches Maximum |
| <b>Shank Style:</b>                    | Straight                                      |
| <b>Head Major Diameter:</b>            | 0.093 Inches Minimum And 0.097 Inches Maximum |
| <b>End Item Identification:</b>        | F/a-18 E/f Aircraft                           |
| <b>Criticality Code Justification:</b> | Agav  |
| <b>Special Features:</b>               | Rivet Is Dimpled 0.020 Inches Maximum         |
| <b>Material:</b>                       | Aluminum Alloy 2117 Overall                   |

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-12D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.