

Description

Fastener Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20470AD514D |
| Minimum Qty (MOQ): | 500 EA |
| NSN: | 5320-01-603-8594 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470AD5-14D Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Head Style: | Oval/truss |
| Head Height: | 0.067 Inches Nominal |
| Shank Diameter: | 0.156 Inches Nominal |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Special Features: | Anodize Per Mil-a-8525 Typeii,class1 Dichromate Seal |
| Material: | Aluminum Alloy 2117 Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.