

Description

Fastener Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD514D
Minimum Qty (MOQ):	500 EA
NSN:	5320-01-603-8594
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS20470AD5-14D Specifications

<b>Fastener Length:</b>	0.865 Inches Minimum And 0.885 Inches Maximum
<b>Head Style:</b>	Oval/truss
<b>Head Height:</b>	0.067 Inches Nominal
<b>Shank Diameter:</b>	0.156 Inches Nominal
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Special Features:</b>	Anodize Per Mil-a-8525 Typeii,class1 Dichromate Seal
<b>Material:</b>	Aluminum Alloy 2117 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-14D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.