



Military-Fasteners.com

P/N MS20470AD5-32D

Description

Fastener Length: 2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD532D
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-510-8259
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20470AD5-32D Specifications

Fastener Length:	2.000 Inches Nominal
Head Style:	Universal
Head Height:	0.054 Inches Nominal
Shank Diameter:	1.249 Inches Minimum And 1.253 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
End Item Identification:	F/a-18e/f
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Rivet, Solid Universal Head, Aluminum Alloy And Titanium Columbium Alloy
Special Features:	Ms20470 Has Been Replaced By Nasm20470 Dated August 18, 1998
Material:	Aluminum Alloy Overall
Material Document And Classification:	(a92117) Per Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty li, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-32D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.