

**Description**

Fastener Length: 2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20470AD532D
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-510-8259
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N MS20470AD5-32D Specifications

<b>Fastener Length:</b>	2.000 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.054 Inches Nominal
<b>Shank Diameter:</b>	1.249 Inches Minimum And 1.253 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.238 Inches Minimum And 0.262 Inches Maximum
<b>End Item Identification:</b>	F/a-18e/f
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	Rivet, Solid Universal Head, Aluminum Alloy And Titanium Columbium Alloy
<b>Special Features:</b>	Ms20470 Has Been Replaced By Nasm20470 Dated August 18, 1998
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	(a92117) Per Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Ty li, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-32D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.