

**Description**

Fastener Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470AD53D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-485-5876
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470AD5-3D Specifications

<b>Fastener Length:</b>	0.178 Inches Minimum And 0.198 Inches Maximum
<b>Head Style:</b>	Brazier
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>End Item Identification:</b>	Launcher, Guided Missile
<b>Criticality Code Justification:</b>	Agav
<b>Part Name Assigned By Controlling Agency:</b>	(inavy) Rivet, Solid Universal Head, Aluminum Alloy And Titanium Columbium Alloy
<b>Special Features:</b>	Has Dimpled Head Centered On Head 0.020 Inches Max Height And 0.030 Inches Max In Diameter To Indicate Aluminum Alloy 2117
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625, Type Ii, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-3D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.