

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD53D
Minimum Qty (MOQ):	1000 EA
NSN:	5320-01-485-5876
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS20470AD5-3D Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Brazier
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
End Item Identification:	Launcher, Guided Missile
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	(inavy) Rivet, Solid Universal Head, Aluminum Alloy And Titanium Columbium Alloy
Special Features:	Has Dimpled Head Centered On Head 0.020 Inches Max Height And 0.030 Inches Max In Diameter To Indicate Aluminum Alloy 2117
Material:	Aluminum Alloy 2117 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625, Type II, Class 1, Dichromate Seal Mil Spec Single Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-3D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.