

**Description**

length: 17/32", diameter: 5/32", universal head, aluminum alloy, roughly 720 pieces per pound

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20470AD585
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-480-5769
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

## P/N MS20470AD5-8.5 Specifications

<b>Fastener Length:</b>	0.521 Inches Minimum And 0.541 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.067 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.155 Inches Minimum And 0.159 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>End Item Identification:</b>	Aircraft (ac130-h, Mc-130h, Ec-130e, Hc-130)
<b>Grip Length:</b>	0.234 Inches Nominal
<b>Special Features:</b>	Chemical Surface Treatment Per Mil-c-5541, Class 1a, Gold/yellow
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas20470 Professional/industrial Association Standard

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-8.5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.