

Description

Fastener Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470AD59D
Minimum Qty (MOQ):	505 EA
NSN:	5320-01-488-6587
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470AD5-9D Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.159 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
End Item Identification:	Ecp277; Harrier
Grip Length:	0.318 Nominal Mils And 0.338 Nominal Centimeters
Shear Strength:	26000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-q-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall And Dichromate Overall
Surface Treatment Document And Classification:	Mil-a-8625, Ty li, Cl 1 Mil Spec All Treatment Responses Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD5-9D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.