

Description

length: 1", diameter: 3/16", universal head, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470AD616 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-00-117-6857 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



P/N MS20470AD6-16 Specifications

| | |
|---|--|
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Shank Diameter: | 0.186 Inches Minimum And 0.191 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.356 Inches Minimum And 0.394 Inches Maximum |
| Grip Length: | 0.709 Inches Minimum And 0.729 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD6-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.