

Description

length: 1/8", diameter: 3/16", universal head - 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470AD62
Minimum Qty (MOQ):	1 Pound
NSN:	5320-01-327-5780
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS20470AD6-2 Specifications

Fastener Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Head Style:	Universal
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Shank Diameter:	0.186 Inches Minimum And 0.191 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.356 Inches Minimum And 0.394 Inches Maximum
Shear Strength:	26000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD6-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.