

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470AD813
Minimum Qty (MOQ):	70 EA
NSN:	5320-01-412-6696
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS20470AD8-13 Specifications

Identification Code Color:	Yellow
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.249 Inches Minimum And 0.253 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2117 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment Document And Classification:	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Overall
Specification/standard Data:	96906-ms20470 Government Specification

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD8-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.