

**Description**

Fastener Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS20470AD813
Minimum Qty (MOQ):	70 EA
NSN:	5320-01-412-6696
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS20470AD8-13 Specifications

<b>Identification Code Color:</b>	Yellow
<b>Fastener Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.107 Inches Minimum And 0.117 Inches Maximum
<b>Shank Diameter:</b>	0.249 Inches Minimum And 0.253 Inches Maximum
<b>Shank Style:</b>	Straight W/radius Chamfered Tip
<b>Head Major Diameter:</b>	0.475 Inches Minimum And 0.525 Inches Maximum
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2117 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541, Class 1a Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	96906-ms20470 Government Specification

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD8-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.