

Description

length: 1/4", diameter: 1/4", universal head - 2117-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470AD84 |
| Minimum Qty (MOQ): | 1 Pound |
| NSN: | 5320-01-009-3610 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470AD8-4 Specifications

| | |
|---|--|
| Fastener Length: | 0.250 Inches Nominal |
| Head Style: | Universal |
| Head Height: | 0.107 Inches Minimum And 0.117 Inches Maximum |
| Shank Diameter: | 0.249 Inches Minimum And 0.254 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.475 Inches Minimum And 0.525 Inches Maximum |
| Shear Strength: | 26000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 2117 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470AD8-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.