

Description

Fastener Length: 5/8, roughly 85 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470B1210
Minimum Qty (MOQ):	50
NSN:	5320-01-165-1379
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20470B12-10 Specifications

Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Universal
Head Height:	0.161 Inches Minimum And 0.171 Inches Maximum
Shank Diameter:	0.374 Inches Minimum And 0.379 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.713 Inches Minimum And 0.787 Inches Maximum
Shear Strength:	24000 Single Pounds Per Square Inch
Heat Treatment:	H-32 Strain Hardened Overall
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470B12-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.