

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470B318
Minimum Qty (MOQ):	1000 EA
NSN:	5320-00-177-7531
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS20470B3-18 Specifications

Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.097 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.178 Inches Minimum And 0.196 Inches Maximum
Heat Treatment:	H-32 Strain Hardened Overall
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall Or Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall Or Mil-a-8625 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470B3-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.