

Description

Fastener Length: 1/2", roughly 2365 pieces per pound, MS20470 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470B38 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-118-1994 |
| Schedule B: | 7616.10.3000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470B3-8 Specifications

| | |
|---|--|
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.097 Inches Maximum |
| Shank Style: | Straight W/radius Chamfered Tip |
| Head Major Diameter: | 0.178 Inches Minimum And 0.196 Inches Maximum |
| Grip Length: | 0.349 Nominal Mils And 0.369 Nominal Centimeters |
| Shear Strength: | 24000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 5056 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470B3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.