

Description

Fastener Length: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | MS20470B424 |
| Minimum Qty (MOQ): | 115 EA |
| NSN: | 5320-00-584-9806 |
| Schedule B: | 7616.10.3000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N MS20470B4-24 Specifications

| | |
|--|--|
| Fastener Length: | 1.490 Inches Minimum And 1.510 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.054 Inches Minimum And 0.064 Inches Maximum |
| Shank Diameter: | 0.124 Inches Minimum And 0.128 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.238 Inches Minimum And 0.262 Inches Maximum |
| Grip Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Shear Strength: | 24000 Single Pounds Per Square Inch |
| Material: | Aluminum Alloy 5056 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall And Chromate Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470B4-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.