

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470B44A
Minimum Qty (MOQ):	505 EA
NSN:	5320-00-119-6823
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N MS20470B4-4A Specifications

Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Shear Strength:	24000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 5056 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470B4-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.