

## P/N MS20470B8-9

### **Description**

Fastener Length: 1/2"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	MS20470B89
Minimum Qty (MOQ):	250 EA
NSN:	5320-00-264-4315
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20470B8-9 Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Universal
Head Height:	0.107 Inches Minimum And 0.117 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight W/radius Chamfered Tip
Head Major Diameter:	0.475 Inches Minimum And 0.525 Inches Maximum
Material:	Aluminum Alloy 5056 Overall
Surface Treatment:	Anodize Overall

## **How to Order**

Order this solid rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/MS20470B8-9">https://military-fasteners.com/rivets/solid+rivets/MS20470B8-9</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.