

Description


length: 9/16", diameter: 5/32", universal head, 2017-t4 aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20470D59
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-241-5982
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



P/N MS20470D5-9 Specifications

Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Universal
Head Height:	0.067 Inches Minimum And 0.077 Inches Maximum
Shank Diameter:	0.155 Inches Minimum And 0.160 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.296 Inches Minimum And 0.328 Inches Maximum
Grip Length:	0.318 Inches Minimum And 0.339 Inches Maximum
Shear Strength:	33000 Single Pounds Per Square Inch
Material:	Aluminum Alloy 2017 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Oxide Film Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470D5-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.