

**Description**

length: 5/8", diameter: 3/16", universal head, 2017-t4 aluminum alloy, roughly 415 pieces per pound, MS20470 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS20470D610
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-117-5857
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N MS20470D6-10 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.191 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Grip Length:</b>	0.334 Inches Minimum And 0.354 Inches Maximum
<b>Shear Strength:</b>	33000 Single Pounds Per Square Inch
<b>Material:</b>	Aluminum Alloy 2017 Overall
<b>Material Document And Classification:</b>	Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Oxide Film Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS20470D6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.